

MATERIAL SAFETY DATA SHEET

HI-WETT® XTRA

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

FORMULATED FOR:

Applied Spray Technologies, LLC
P.O. Box 200118, Evans, CO 80620

24-Hour Emergency Phone: 1-970-371-3361
Medical Emergencies: 1-800-222-1222
U.S. Coast Guard National Response Center: 1-800-424-8802

PRODUCT NAME: HI-WETT™ XTRA
CHEMICAL NAME: Synthetic Latex (combination of synthetic latex and organosilicone surfactant fluid)
CHEMICAL FAMILY: Sticker-Surfactant-Deposition Agent
CALIF. REG. NO.:
WASH. REG. NO.: 99915-06001
MSDS Number: HWX-06-AST MSDS Revisions: New Date Of Issue: 10/13/06 Supersedes: New

2. HAZARDS IDENTIFICATION SUMMARY

KEEP OUT OF REACH OF CHILDREN - CAUTION – Harmful if swallowed. Avoid breathing vapors.

This product is pale green liquid with mild odor.

3. COMPOSITION, INFORMATION ON INGREDIENTS

<u>Chemical Ingredients:</u>	<u>Percentage by Weight:</u>	<u>CAS No.</u>	<u>TLV (Units)</u>
Synthetic Latex and organosilicone surfactant fluid	63.40	Mixture	none established
Other Ingredients	36.60		

4. FIRST AID MEASURES

If in Eyes: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.
If on Skin or Clothing: Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.
If Swallowed: Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
If Inhaled: Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.

5. FIRE FIGHTING MEASURES

FLASH POINT (°F/Test Method): >212°F / >100°C (PMCC)
FLAMMABLE LIMITS (LFL & UFL): Not established
EXTINGUISHING MEDIA: Foam, Dry chemical, CO₂, or water spray.
HAZARDOUS COMBUSTION PRODUCTS: None known.
SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained breathing apparatus and full protective gear.
UNUSUAL FIRE AND EXPLOSION HAZARDS: Dike area to contain run-off and prevent contamination of water supplies. Burning may produce toxic fumes, carbon monoxide, carbon dioxide and oxides of silicon.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Wear appropriate personal protective equipment (refer to Section 8) when responding to spills. Shut off source of leak if safe to do so. Dike and contain spill. Soak up residue with absorbent such as clay, sand or other suitable material and dispose of properly. Flush area with water to remove trace residue. Contain runoff from residue flush and dispose of properly. Place in container for proper disposal. Check local, state and federal regulations for proper disposal.

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

7. HANDLING AND STORAGE

HANDLING: Wear impervious gloves when handling. Keep away from heat, sparks, and flames while in use. Wash with soap and water before eating, drinking, smoking, applying cosmetics, or using toilet facilities. Keep away from children, feed and foodstuffs, fertilizers and seed.

STORAGE: Store in a cool, dry place. Store in original container. Keep container tightly closed. Do not reuse empty container. Do not contaminate water, food or feed by storage or disposal.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Not required.
RESPIRATORY PROTECTION: Wear a NIOSH approved respirator if necessary.
EYE PROTECTION: Chemical goggles or shielded safety glasses.
SKIN PROTECTION: Wear protective clothing. Wear impervious rubber or chemical-resistant gloves.

For product	OSHA PEL 8 hr TWA not established	ACGIH TLV-TWA not established
-------------	---	---

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOR: Pale green liquid with mild odor	BULK DENSITY: 8.57 lbs/gal.	SOLUBILITY: Dispersible
SPECIFIC GRAVITY (Water = 1): 1.027 g/ml	BOILING POINT: Not established	pH: 7.3 (1% solution)
VAPOR PRESSURE: Not established	EVAPORATION RATE: Not established	
PERCENT VOLATILE (by volume): Not established		

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guaranteed analysis of any specific lot or as specification items.

10. STABILITY AND REACTIVITY

STABILITY: Stable
CONDITIONS TO AVOID: None known.
INCOMPATIBILITY: Avoid contact with strong oxidizers, strong acids and bases at high temperatures.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide from burning.
HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

Acute Oral LD₅₀ (rat): >5000 mg/kg [EPA Category IV]	Acute Dermal LD₅₀ (rabbit): >2000 mg/kg [EPA Category IV]
Eye Irritation (rabbit): Mild to moderate irritant [EPA Category III]	Skin Irritation (rabbit): Not a skin irritant [EPA Category IV]
Inhalation LC₅₀ (rat): >0.19 mg/L (4 HR)	Skin Sensitization (guinea pig): Not a sensitizer.
Carcinogenic Potential: None listed by OSHA, NTP, IARC, and ACGIH as a carcinogen	

12. ECOLOGICAL INFORMATION

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash waters.

13. DISPOSAL CONSIDERATIONS

Do not reuse product containers. Triple rinse (or equivalent), adding rinse water to spray tank, then offer for recycling at an ACRC site (go to <http://www.acrecycle.org> for locations) or by reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. Do not contaminate water, food or feed by storage or disposal.

14. TRANSPORT INFORMATION

DOT Shipping Description: NOT REGULATED BY USDOT.
Freight Classification: ADHESIVES, ADJUVANTS, SPREADERS OR STICKERS (NMFC 4610; CLASS: LTL 60, TL 35)
Consult appropriate ICAO/IATA and IMDG regulations for shipment requirements in the Air and Maritime shipping modes.

15. REGULATORY INFORMATION

NFPA & HMIS Hazard Ratings:	NFPA		HMIS
	2 Health	0 Least	2 Health
	1 Flammability	1 Slight	1 Flammability
	0 Instability	2 Moderate	0 Reactivity
		3 High	H PPE
		4 Severe	

MATERIAL SAFETY DATA SHEET

HI-WETT® XTRA

SARA Hazard Notification/Reporting

SARA Title III Hazard Category: Immediate Y Fire N Sudden Release of Pressure N
Delayed N Reactive N

Reportable Quantity (RQ) under U.S. CERCLA: Not listed

SARA, Title III, Section 313: Not listed

RCRA Waste Code: Not listed

CA Proposition 65: Not listed

16. OTHER

MSDS STATUS: New

PREPARED BY: Registrations and Regulatory Affairs

REVIEWED BY: Environmental/ Regulatory Services

Hi-Wett is a trademark of Elliott Chemicals, Inc.

Although the information and recommendations set forth herein (hereinafter "Information") are presented in good faith and believed to be correct, Applied Spray Technologies, LLC., the manufacturer or the seller makes no representations as to the completeness or accuracy thereof. Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use.

The product covered by this information sheet is furnished "as is" by Applied Spray Technologies, LLC., the manufacturer or the seller, and is subject only to the warranties, if any, that appear on the product's label or are otherwise expressly provided herein.

Except as expressly provided on the product's label or otherwise provided herein, no warranties, guarantees, or representations of any kind, either express or implied, or by usage of trade, statutory or otherwise, are made by Applied Spray Technologies, LLC., the manufacturer or the seller with regard to the product or use of the product, including, but not limited to, merchantability, fitness for a particular purpose, use or eligibility of the product for any particular trade usage.

Except as expressly stated herein, Applied Spray Technologies, LLC., the manufacturer or the seller makes no warranty of results to be obtained by use of the product covered by this information. Buyer's or user's exclusive remedy, and the total liability of Applied Spray Technologies, LLC., the manufacturer or the seller, shall be limited to damages not exceeding the cost of the product. No agent or employee of Applied Spray Technologies, LLC., the manufacturer or the seller is authorized to amend the terms of this warranty disclaimer or the product's label or to make a representation or recommendation different from or inconsistent with the label of this product.

IN NO EVENT SHALL APPLIED SPRAY TECHNOLOGIES, LLC., THE MANUFACTURER OR THE SELLER BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE USE, HANDLING, APPLICATION, STORAGE OR DISPOSAL OF THIS PRODUCT OR FOR DAMAGES IN THE NATURE OF PENALTIES AND THE BUYER AND USER WAIVE ANY RIGHT THEY MAY HAVE TO SUCH DAMAGES.